

TECHNICAL DATA

Fluke 88V Deluxe Automotive Multimeter



Key features

- Pulse width, duty cycle, Min/Max/Avg recording
- 10 meg ohm input impedance won't damage computer circuits
- Large display and bright backlight for increased visibility

Product overview: Fluke 88V Deluxe Automotive Multimeter

The Fluke 88V meter has measurement functions, troubleshooting features, and accuracy levels needed to solve problems on conventional and hybrid vehicles. The 88V is the most powerful automotive multimeter ever offered by Fluke. In addition to standard multimeter features such as the ability to measure voltage, current, continuity, and resistance, the 88V can perform:

Pulse width

Duty cycle

Min/Max/Average recording

Diode tests

The pulse width function provides millisecond resolution for troubleshooting fuel injectors.

Automotive measurements

The 88V meter can take care of many automotive needs, getting into more of the digital multimeters measurement capabilities - it can measure voltage up to 1000 V AC and DC, current up to 10 A, 20 A for up to 30 seconds and frequency to 200 kHz and % duty cycle. Add those features to RPM measurements with optional inductive pickup and millisecond pulse width measurements for fuel injectors to name a few. The 88V comes packed with the functions you need:

Temperature measurements with optional temperature probe

Analog bar graph to track changing or unstable signals

Min/Max/Average recording with Min/Max Alert to capture variations automatically

Peak Min/Max to record transients as fast as 250 μ s

88V multimeter designed for the garage

While working in a garage, the large display digits can help you focus on the vehicle while still being able to read the numbers. Plus, the two-level bright white backlight offers the additional visibility you may need.

An optional magnetic hanger lets you hang the meter from most steel surfaces for easy set-up and viewing. The 88V is designed to be used in high energy environments like those found on hybrid vehicles.

The product is supported by a limited lifetime warranty.

Specifications: Fluke 88V Deluxe Automotive Multimeter

Technical Specifications		
DCV	Maximum voltage	1000 V
	Accuracy	$\pm(0.1\% + 1)$
	Best resolution	0.01 mV
ACV	Maximum voltage	1000 V
	Accuracy	$\pm(0.5\% + 2)$
	AC bandwidth	5 kHz
	Best resolution	0.01 mV
DC current	Maximum amps	10 A
	Amps accuracy	$\pm(0.4\% + 2)$
	Best resolution	0.001 mA
AC current	Maximum amps	10 A
	Amps accuracy	$\pm(1.2\% + 2)$
	Best resolution	0.001 mA
Resistance	Maximum resistance	50 M Ω
	Accuracy	$\pm(0.4\% + 1)$
	Best resolution	0.1 Ω

Capacitance	Maximum capacitance	9,999 μ F
	Accuracy	$\pm(1\% + 2)$
	Best resolution	0.01 nF
Frequency	Maximum frequency	200 KHz
	Accuracy	$\pm(0.005\% + 1)$
	Best resolution	0.01 Hz
Duty cycle	Maximum duty cycle	99.9%
	Accuracy	within 2% per KHz + 0.1%
	Best resolution	0.1%
Temperature measurement	-200.0°C – 1090°C -328.0°F – 1994.0°F, 1.0% excluding probe	
80 BK temperature probe	-40 °C – 260°C -40 °F – 500°F, 2.2°C or 2% whichever is greater	
Conductance	Maximum conductance	60.00 nS
	Accuracy	$\pm(1.0\% + 10)$
	Maximum resolution	0.01 nS
Operating range	Operating temperature	-20°C – 55°C
	Storage temperature	-40°C – 60°C
Physical	5.2 x 9.8x 20.1 cm (2.06 x 3.86 x 7.93 in) 624 g (22 oz.)	

Ordering information



Fluke 88V

Fluke 88V Deluxe Automotive Multimeter

Includes:

- Fluke 88V digital multimeter
- High-impact holster
- Test leads

Fluke. *Keeping your world up and running.®*

Fluke Europe B.V.

P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en

©2021 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
12/2021

For more information call:

In Middle East/Africa
+31 (0)40 267 5100

**Modification of this document is not permitted
without written permission from Fluke Corporation.**